

TEST REPORT

No.: SP100804721 Date: Sept.10,2014

Page: 1 of 3

The following sample(s) was/ were submitted and identified on behalf of the client as:

Sample Name : ALUMINIUM COMPOSITE PANEL

Sample No. SP100804721 Product specification : 2440*1220*3MM

Brand : TWILDOND

Test Required : To determine the flammability (building materials class B2) in accordance with

DIN 4102-1 (May 1998) Fire behaviour of building materials and elements Part 1:

Classification of building materials, Requirements and testing

Date of Receipt Aug.23,2014

Test Period Aug.23,2014 to Sept.10,2014

Test result(s) : For further details, please refer to the following page(s)

****** To be continued******

Signed for SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd

Authorized signatory

y the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/terms_and_conditions, mat documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.thm. Attention is drawn to the limitation of nd jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings_at the time of thin the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction ghts and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, on, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

The results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



TEST REPORT

No.: SP100804721 Date: Sept.10,2014

Page: 2 of 3

I. Test conducted

This test was conducted as per DIN 4102-1:1998 Clause 6.2. Classification in according to DIN 4102-1 (May 1998) Clause 6.2. Class B2 materials

II. Sample details

General description	Aluminium Composite Panel
Color / Density	White / 4.1kg/m ²
Size of Sample	190×90mm×3mm

Conditioning

Prior to testing, the sample was conditioned at least 14 days to constant mass at a temperature of 23 ± 2 °C, and a relative humidity of 50 \pm 6 %.

III. Test results

Normal Flammability Test according to DIN 4102-1 Clause 6.2

<u>Flame application:</u> [$\sqrt{\ }$] bottom edge ignition, [] surface ignition

Specimen No.	1	2	3	4	5
Reaching the measuring mark within 20 seconds	No	No	No	No	No
Self extinguishing of the flame (s)	15	15	15	15	15
Max. flame height (cm)	2	2	2	2	2
End of afterflaming (s)	0	0	0	0	0
End of afterglowing (s)	0	0	0	0	0
Molten dripping	No	No	No	No	No
Smoke developments (visual impression)	Slight				

All timings are from start of testing

Comments:

[√] DIN 4102-B2; [] DIN 4102-B3

Criteria for classification for Class B2 (DIN 4102-1 Clause 6.2.2)

All materials, may be classed as B2 materials if they,

Pass DIN 4102-1 Clause 6.2.3 Ignitability Test

For each specimen, flaming doesn't reach the gage mark within 20s after flame application.

****** To be continued******

y the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/terms_and_conditions, mat documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of diffusion of a diffusion of the second of the se



TEST REPORT

No.: SP100804721 Date: Sept.10,2014

Page: 3 of 3

Conclusion: The tested sample meets the Normal flammability requirements of class B2 of building materials under DIN 4102-1 (May 1998).

STATEMENTS:

This test report does not replace any mandatory certification of the product that may be required.

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire and smoke hazard of the product in use.

Sample Photo:



The test was performed by SGS internal laboratory.

****** End of report ******

document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/terms_and_conditions, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of lifty terms—and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of search of the time of the search of the se