

## 1 Identification

**Product Name:** PAPER OVERLAID PLYWOOD

**Other Means of Identification:** Mixture

**Recommended Use of the Chemical and Restriction on Use:** Building material

**Details of Manufacturer or Importer:**

Gunneresen Pty Ltd  
112 Salmon Street,  
Port Melbourne VIC 3207 AU

**Phone Number:** 03 9647 9972

**Emergency telephone number:** National Poison Information Centre: 13 11 26

## 2 Hazard(s) Identification

### Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)



health hazard

Carcinogenicity 1B                      H350 May cause cancer.



Acute Toxicity (Inhalation) 4    H332 Harmful if inhaled.

Skin Sensitisation 1                      H317 May cause an allergic skin reaction.

**Signal Word** Danger

### Hazard Statements

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

### Precautionary Statements

P201                      Obtain special instructions before use.

P202                      Do not handle until all safety precautions have been read and understood.

P261                      Avoid breathing dust/fume/gas/mist/vapours/spray.

P271                      Use only outdoors or in a well-ventilated area.

P272                      Contaminated work clothing should not be allowed out of the workplace.

P280                      Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312                      Call a POISON CENTER/doctor if you feel unwell.

P321                      Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P405                      Store locked up.

P501                      Dispose of contents/container in accordance with local/regional/national regulations.

(Contd. on page 2)

# Safety Data Sheet

## according to WHS Regulations

Printing date 25.03.2019

Revision: 25.03.2019

**Product Name: PAPER OVERLAID PLYWOOD**

(Contd. of page 1)

### 3 Composition and Information on Ingredients

**Chemical Characterization: Mixtures****Description:**

This product consists of paper overlaid plywood. This product may contain small quantities of formaldehyde present in the adhesive.

**Hazardous Components:**

CAS: 50-00-0	Formaldehyde	<2%
	⚠ Acute Toxicity (Oral) 3, H301; Acute Toxicity (Dermal) 3, H311; Acute Toxicity (Inhalation) 2, H330; ⚠ Carcinogenicity 1B, H350; ⚠ Skin Corrosion/Irritation 1B, H314; Serious Eye Damage/Irritation 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sensitisation 1, H317; Aquatic Acute 2, H401	
CAS: 9004-34-6	Cellulose	<2%

### 4 First Aid Measures

**Inhalation:** If inhaled, remove to fresh air. Seek medical attention if breathing problems develop.

**Skin Contact:**

In case of skin contact, wash affected areas with water and soap. Seek medical attention if symptoms occur.

**Eye Contact:**

In case of eye contact, hold eyelids open and rinse with water. Seek medical attention if symptoms occur.

**Ingestion:**

If swallowed, do not induce vomiting. Rinse mouth with water. Give a glass of water. Seek medical attention if symptoms occur.

**Symptoms Caused by Exposure:**

**Inhalation:** Harmful if inhaled. Inhalation of dusts may cause irritation and shortness of breath.

**Skin Contact:** Dusts may cause irritation or an allergic skin reaction.

**Eye Contact:** Dusts may cause eye irritation.

**Ingestion:** May cause gastrointestinal irritation.

### 5 Fire Fighting Measures

**Suitable Extinguishing Media:** Use fire extinguishing methods suitable to surrounding conditions.

**Specific Hazards Arising from the Chemical:**

Hazardous combustion products include oxides of carbon and other typical pyrolysis products.

This product may burn in a fire. Sawing, sanding or machining produces dust which may form flammable or explosive mixtures in air.

Product close to fire should be removed if safe to do so.

**Special Protective Equipment and Precautions for Fire Fighters:**

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

### 6 Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:**

Ensure adequate ventilation. Avoid generating dust. Do not breathe dust.

**Environmental Precautions:**

In the event of a major spill, prevent spillage from entering drains or water courses.

**Methods and Materials for Containment and Cleaning Up:**

Pick up large pieces and clean up the small pieces and dusts with a vacuum or by sweeping.

(Contd. on page 3)

# Safety Data Sheet

## according to WHS Regulations

Printing date 25.03.2019

Revision: 25.03.2019

**Product Name: PAPER OVERLAID PLYWOOD**

(Contd. of page 2)

### 7 Handling and Storage

**Precautions for Safe Handling:**

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of dust. Use correct manual handling procedures when lifting heavy loads.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

**Conditions for Safe Storage:**

Store in a cool, dry and well ventilated area. Protect from heat, sparks, open flames and other sources of ignition. Avoid prolonged storage in direct sunlight. Keep away from strong oxidising agents.

### 8 Exposure Controls and Personal Protection

**Exposure Standards:****CAS: 50-00-0 Formaldehyde**

NES	STEL: 2.5 mg/m <sup>3</sup> , 2 ppm TWA: 1.2 mg/m <sup>3</sup> , 1 ppm Sen
-----	--

WES	STEL: 2.5 mg/m <sup>3</sup> , 2 ppm TWA: 1.2 mg/m <sup>3</sup> , 1 ppm Sen
-----	--

**CAS: 9004-34-6 Cellulose**

NES	TWA: 10 mg/m <sup>3</sup>
-----	---------------------------

WES	TWA: 10 mg/m <sup>3</sup>
-----	---------------------------

**Engineering Controls:**

Maintain air concentration below occupational exposure standards, providing adequate ventilation.

**Respiratory Protection:**

Where an inhalation risk exists, wear a Class P1 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information.

**Skin Protection:**

Leather/pigskin, neoprene or nitrile gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting hand protection, the product should comply with relevant performance criteria. For example, gloves should meet a suitable level of abrasion resistance to provide protection against hazards of a workplace.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

**Eye and Face Protection:**

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

### 9 Physical and Chemical Properties

**Appearance:**

<b>Form:</b>	Solid
<b>Colour:</b>	Various
<b>Odour:</b>	Slight

(Contd. on page 4)

# Safety Data Sheet

## according to WHS Regulations

Printing date 25.03.2019

Revision: 25.03.2019

**Product Name: PAPER OVERLAID PLYWOOD**

(Contd. of page 3)

<b>Odour Threshold:</b>	No information available
<b>pH-Value:</b>	No information available
<b>Melting point/freezing point:</b>	No information available
<b>Initial Boiling Point/Boiling Range:</b>	No information available
<b>Flash Point:</b>	No information available
<b>Flammability:</b>	Product is not flammable.
<b>Auto-ignition Temperature:</b>	No information available
<b>Decomposition Temperature:</b>	No information available
<b>Explosion Limits:</b>	
<b>Lower:</b>	No information available
<b>Upper:</b>	No information available
<b>Vapour Pressure:</b>	No information available
<b>Density:</b>	No information available
<b>Relative Density:</b>	No information available
<b>Vapour Density:</b>	No information available
<b>Evaporation Rate:</b>	No information available
<b>Solubility in Water:</b>	Insoluble
<b>Partition Coefficient (n-octanol/water):</b>	No information available

### 10 Stability and Reactivity

**Possibility of Hazardous Reactions:** Hazardous polymerisation will not occur.

**Chemical Stability:** Stable at ambient temperature and under normal conditions of use.

**Conditions to Avoid:** Heat, sparks, open flames and other sources of ignition.

**Incompatible Materials:** No further relevant information available.

**Hazardous Decomposition Products:** Oxides of carbon and other typical pyrolysis products.

### 11 Toxicological Information

**Toxicity:**

**LD<sub>50</sub>/LC<sub>50</sub> Values Relevant for Classification:**

**CAS: 50-00-0 Formaldehyde**

Oral	LD <sub>50</sub>	>200 mg/kg (rat)
------	------------------	------------------

**Acute Health Effects**

**Inhalation:** Harmful if inhaled. Inhalation of dusts may cause irritation and shortness of breath.

**Skin:** Dusts may cause irritation or an allergic skin reaction.

**Eye:** Dusts may cause eye irritation.

**Ingestion:** May cause gastrointestinal irritation.

**Skin Corrosion / Irritation:** Based on classification principles, the classification criteria are not met.

**Serious Eye Damage / Irritation:** Based on classification principles, the classification criteria are not met.

**Respiratory or Skin Sensitisation:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.

**Carcinogenicity:**

May cause cancer.

Formaldehyde is classified by IARC as Group 1 - Carcinogenic to humans.

Polyvinyl acetate is classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

**Reproductive Toxicity:** Based on classification principles, the classification criteria are not met.

(Contd. on page 5)

# Safety Data Sheet

## according to WHS Regulations

Printing date 25.03.2019

Revision: 25.03.2019

**Product Name: PAPER OVERLAID PLYWOOD**

(Contd. of page 4)

**Specific Target Organ Toxicity (STOT) - Single Exposure:**

Based on classification principles, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Based on classification principles, the classification criteria are not met.

**Aspiration Hazard:** Based on classification principles, the classification criteria are not met.**Chronic Health Effects:** No information available**Existing Conditions Aggravated by Exposure:** No information available**Additional toxicological information:** No information available

### 12 Ecological Information

**Ecotoxicity:****Aquatic toxicity:** No further relevant information available.**Persistence and Degradability:** No further relevant information available.**Bioaccumulative Potential:** No further relevant information available.**Mobility in Soil:** No further relevant information available.**Other adverse effects:** No further relevant information available.

### 13 Disposal Considerations

**Disposal Methods and Containers:** This product can be disposed of as household waste.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

### 14 Transport Information

**UN Number** Not regulated**Proper Shipping Name** Not regulated**Dangerous Goods Class** Not regulated**Packing Group:** Not regulated

### 15 Regulatory Information

**Australian Inventory of Chemical Substances:**

CAS: 50-00-0	Formaldehyde
CAS: 9004-34-6	Cellulose
CAS: 9003-20-7	Poly(vinyl acetate)

**Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:**

Not Scheduled.

### 16 Other Information

**Date of Preparation or Last Revision:** 25.03.2019**Prepared by:** MSDS.COM.AU Pty Ltd[www.msds.com.au](http://www.msds.com.au)**Abbreviations and acronyms:**

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 6)

# Safety Data Sheet

## according to WHS Regulations

Printing date 25.03.2019

Revision: 25.03.2019

**Product Name: PAPER OVERLAID PLYWOOD**

(Contd. of page 5)

LC<sub>50</sub>: Lethal concentration, 50 percentLD<sub>50</sub>: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Acute Toxicity (Oral) 3: Acute toxicity – Category 3

Acute Toxicity (Inhalation) 2: Acute toxicity – Category 2

Acute Toxicity (Inhalation) 4: Acute toxicity – Category 4

Skin Corrosion/Irritation 1B: Skin corrosion/irritation – Category 1B

Serious Eye Damage/Irritation 1: Serious eye damage/eye irritation – Category 1

Skin Sensitisation 1: Skin sensitisation, Hazard Category 1

Carcinogenicity 1B: Carcinogenicity – Category 1B

Aquatic Acute 2: Hazardous to the aquatic environment, short-term (Acute). Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term (Chronic). Category 2

**Disclaimer**

This SDS is prepared in accord with the Safe Work Australia document “Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - February 2016”

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Gunnensen Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.